

Technical Datasheet of Flexible Cables			LDIS09CYUAYL004C095S
Sr.No.	Description	Unit	4C X 95 Sq. mm.
1	Manufacturer Name		Polycab Wires Private Limited
2	Brand Name		POLYCAB
3	Rated Voltage		1100V
4	CONDUCTOR		
	a) Material		Plain annealed high conductivity Flexible copper conductor as per Class 5 of IS 8130/2013 latest
	b) Conductor Size	Sq.mm	95.0
	c) Max. D.C Cond. Resistance at 20 Deg. C.	Ohm/km	0.206
5	INSULATION		
	a) Material		HR-PVC Type 'C'
	b) Nominal Thickness in mm.	mm	1.6
	c) Core Identification		Red, Yellow, Blue & Black
6	Sheath		
	Material		Extruded FR-LSH PVC Type 'ST2' as per IS:5831/84
	Nominal Thickness in mm.		2.4
	Sheath Colour		Black
	FR-LSH PROPERTIES		
	Oxygen Index		Min. 29% as per ASTM D- 2863
	Temperature Index		Min. 250 Deg.C as per ASTM D- 2863
	Smoke Density Rating		Max. 60% as per ASTM D- 2843
	Acid Gas Generation		Max. 20% as per IEC- 754- 1
7	Maximum Overall Diameter	mm	50.2
8	Current rating	Amps	240
9	Max. conductor temp. under normal operating conditions	°C	85°C
10	Max conductor temp at the termination of short circuit	°C	160°C
11	Standards to which the cables confirm		As per IS 8130/2013,IS 694/2010, etc. with latest up to date amendments
12	Recommended minimum bending radius in mm		8 times the overall diameter of the cable
13	Max. Tensile strength when pulled with pulling eye	Kg	1936
14	Printing		POLYCAB 1100 V, NO.OF CORE X SQ.MM HR-FR-LSH